



designed for scientists



## T 25 digital Package

/// Data Sheet

This T25 Digital Package contains:

1 \* T 25 digital ULTRA-TURRAX® - Disperser

1 \* S 25 N - 18 G - Dispersing Element Ø18 mm

1 \* R1826 Plate stand, H800 mm

[www.ika.com](http://www.ika.com)

Subject to technical changes





designed for scientists

1 \* R 182 Boss head clamp, clamping range Ø6-16 mm





designed for scientists

### Technical Data

|  |                       |
|--|-----------------------|
| Motor rating input [W]                     | 800                   |
| Motor rating output [W]                    | 500                   |
| Volume range (H <sub>2</sub> O) [l]        | 0.001 - 2             |
| Viscosity max. [mPas]                      | 5000                  |
| Speed range [rpm]                          | 3000 - 25000          |
| Speed deviation [%]                        | 1                     |
| Speed control                              | stepless              |
| Speed display                              | LED                   |
| Noise without element [dB(A)]              | 75                    |
| Extension arm diameter [mm]                | 13                    |
| Extension arm length [mm]                  | 160                   |
| Process type                               | batch                 |
| Permissible ON time [%]                    | 100                   |
| Dimensions (W x H x D) [mm]                | 87 x 271 x 106        |
| Weight [kg]                                | 2.5                   |
| Permissible ambient temperature [°C]       | 5 - 40                |
| Permissible relative humidity [%]          | 80                    |
| Protection class according to DIN EN 60529 | IP 20                 |
| Voltage [V]                                | 220 - 240 / 100 - 120 |
| Frequency [Hz]                             | 50/60                 |
| Power input [W]                            | 800                   |

